





Specifications (Subject to change)	Seeders models - No Till - Modelos de sembradoras			
	Abati Titanium BDS 3000	Abati Titanium BDS 5000	Abati Titanium BDS 7000	AbaTI Titanium BDS 8000
Pictures				
Separation lines	16 a 190 mm.	26 a 190 mm.	36 a 190 mm.	40 a 190 mm.
Optional lines	Adjustable			
Front line	380 / 350 mm.			
Rear line	380 / 350 mm.			
Distances between lines	1230 mm.			
Clearing soil	320 mm.			
Row type	Mono disc			
Weight row unitary	92 kilogramos			
Disc	18" x 5 mm.			
Disc inclination	Angle 7°			
Independent double boot	Seed and Fertilizer			
Compactor wheel	10" x 1"			
Leveling wheel	4,5" x 15"			
Depth control	De 5 a 100 mm.			
Coverage wheel	Simple			
Capped pressure	12 kgrs. a 42 kgrs.			
Pressure regulator	Five positions			
Coverage wheel optional	Double			
Working width	3040 mm.	4940 mm.	6840 mm.	7600 mm.
Total width	3250 mm.	5100 mm.	6930 mm.	8100 mm.
Seeds hoppers (liters)	775	1150	1640	1950
Fertilizer hoppers (liters)	645	970	1375	1620
Seed pastures hoppers (liters)	110	175	280	280
Total capacity hoppers (liters)	1530	2295	3295	3850
Spedd box: Seeds and fertilizer	Two (54 speeds)			
Regulator box seeds of pastures	One (12 speeds)			
Independent wheel control	One (650 x 16" R1)			
Dispenser seeds and fertilizer	Independent			
Empty weight	3950 kgrs.	5900 kgrs.	7800 kgrs.	8400 kgrs.
Machine weight loaded approx.	4424 kgrs.	7736 kgrs.	10436 kgrs.	11480 kgrs.
Tires	Two (400/60 x 15.5)	Four (400/60 x 15.5)		
Transport system	Frontal two points	Longitude		
Minimum potency tractor	70 HP.	110 HP.	140 HP.	160 HP.
Some crop sowing	Wheat, canola, soya, etc.			

ABATI SA AUSTRALIA - WAREHOUSE MACHINERY AND SPARE PARTS

Shepparton: 355 Midland Hwy, Shepparton VIC 3631

Managing Director and Sales: Raúl José Abati

Mobile Au: + 61 0459 529 259

E-mail: info@abatititanium.com.au

