



**TECHNICAL SPECIFICATIONS
SEEDERS MODEL NO TILL AIR DRILL
SN 9000 30 ft.**

# ROW UNITS	48
Opcional lines spacing adjustment	7" inch min. 190 mm. 13" inch max. 330 mm.
Distance from front row to back row	1230 mm.
Clearance for transport / Soil	320 mm.
Type of row unit and disc size	Single disc (18" inch x 5 mm.)
Disc angle	7° angle incline
Weight of each row unit	92 kgrs.
Seed boot type (double tube)	Seed and fertiliser
Rubber seed press wheel	10" x 1"
Rubber depth control limiter	4.5" x 15" Open clear
Sowing depth range	5 mm. to 100 mm.
Closing wheel adjustmen	Simple
Presure of closing wheel settings	12 kgrs. to 42 kgrs. 5 position
Optional wheel closing adjustment	Double
Down presure of active hydraulic unit	60 kgrs. to 250 kgrs. per row unit
Sowing width	9000 mm.
Overall width	9160 mm.
Weight (empty)	9200 kgrs.
Tyres sizes	8 (400/60 15.5)
Transport system	Front
Tractor power requirement (4 hp. per row unit)	180 HP.

Abati has been dealing with the Australian farming market for six years and has delivered more than 50 No Till seeding machines and continues to strive alongside the Australian farmers. Abati Titanium, the Pioneers of No Till seeding system in South America for 25 years.